

525

Full- and part-circle gear-driven sprinkler 1/2" male thread



FEATURES AND BENEFITS

- Full- or part-circle gear-driven sprinkler with mechanism for quiet operation
- Water lubrication ensures reliable, long-lasting operation.
- Color-coded adjustable parts for easy identification
- Removable filter screen eliminates nozzle clogging.
- User-friendly, fingertip adjustment to full- or part-circle sprinklers
- Baffle deflector allows radius adjustment: 5.0 - 11.5 m
- Color-coded nozzles

TECHNICAL DATA

- Spacing between sprinklers: up to 12.0 m
- Operating pressure: 2.0 - 4.0 bar

525 Performance Table

Nozzle color (mm)	P (bar)	Q (m ³ /h)	D (m)
2.0	2.0	0.51	23
	3.2	0.63	25
Orange	3.0	0.72	26
	4.0	0.57	24
3.2* Green	2.0	0.70	26
	4.0	0.81	27
4.0* Red	2.0	0.85	25
	3.0	1.03	27
	4.0	1.18	28

*Standard nozzle

Postadress:

TRÄDGÅRDSTEKNIK AB
Helsingborgsvägen 578, Varalöv
262 96 ÄNGELHOLM

Telefon : 0431-222 90
Bg.nr : 5743-7980
Org.nr : 556409-6120

URL:

www.tradgardsteknik.se
E-postadress:
info@tradgardsteknik.se