





# V33KH

AGG. 11/20

3~ 50 Hz. 400V	
<b>KOHLER ENGINES</b>	
EU STAGE 5	
69 dB(A) @ 7 mt	
120 lt	

PRIME POWER		STAND-BY POWER	
kVA	kW	kVA	kW
<b>33</b>	<b>26,4</b>	<b>36,3</b>	<b>29</b>

ENVIRONMENTAL CONDITIONS	
Temperature	<b>40° C</b>
Height	<b>1000 mslm</b>
Humidity	<b>60%</b>

**OPEN VERSION B100**

**SOUNDPROOF VERSION C100**


The image is only for demonstration purposes

WEIGHT	DIMENSIONS		
	L [mm]	W [mm]	H [mm]
kg			
<b>785</b>	<b>2100</b>	<b>1000</b>	<b>1800</b>

WEIGHT	DIMENSIONS		
	L [mm]	W [mm]	H [mm]
kg			
<b>1040</b>	<b>2300</b>	<b>1050</b>	<b>1590</b>

## TECHNICAL DETAILS

ELECTRICAL DATA	Electrical system type	3F+N	~
	Power factor	0,8	φ
	Voltage	400	V
	Frequency	50	Hz
	PRP Ampere rating	47,6	A
ENGINE	Engine	KOHLER KDI 1903TCR	
	Engine emissions standard (REG. UE 2016/1628)	EU STAGE 5	
	RPM governor	Electronic	
	Performance class	G3	
	Rpm	1500	rpm
	Nr. of cylinders	3	
	Bore x stroke	88 x 102	mm
	Displacement	1861	cc
	Induction system	Turbocharged	
	Cooling system	Water	
	Engine net prime power	41,3 (30,8)	Hp (kW)
Exhaust gas aftertreatment	DOC + DPF		
CONSUMPTION	Fuel type	Diesel	
	Consumption @ 50-75-100% load	4,4 – 6,3 – 8,5	lt/h
	Standard tank capacity	120	lt
	Autonomy @ 75% load	19	h
ALTERNATOR	Alternator	STAMFORD – MECC ALTE – MARELLI MOTORI	
	Type	Self excited, brushless	
	Number of poles	4	
	Insulation class	H	
	Temperature rise class	H	
	Voltage regulation	AVR	
	Voltage precision	± 1	%
GENERAL	Sound level (soundproof version)	69	dB(A) 7mt
	Exhaust pipe diameter	76	mm
	Electrical system voltage	12	V

## ELECTRIC PANEL

MANUAL

AUTOMATIC MAINS FAILURE



Electronic control unit with multimeter	COMAP AMF25	COMAP AMF25
Electrical panel enclosure protection degree	IP44	
ON-OFF electric panel switch	Key type	Without key
Emergency pushbutton	STANDARD	
Battery charge maintainer	/	12V 3A
Power supply	ECC IP67 sockets: n.1 3P 16A + n.1 5P 63A	Full power terminal
Circuit breaker	Magnetothermal type 1P+N 16A and 4P 50A	Magnetothermal type 4P 50A
Main protection alarms	Min-max V and Hz. LOP. HWT. Battery charger alternator failure. Low fuel level	

## STANDARD ELECTRONIC CONTROL UNIT

COMAP  
AMF25



Functions: automatic or manual start, remote start, periodic test

Multimeter V (L1, L2, L3, N), A (L1, L2, L3), Hz, kVA, battery V, hour counter

Backlit LCD display. USB port

Communication accessories available: Ethernet, GSM-GPRS, 4G, GPS

MODBUS and SNMP communication protocols support

Advanced PLC configurability


## OPTIONAL ELECTRONIC CONTROL UNIT





DEEP SEA DSE7320 MKII

## SOUNDPROOF AND WEATHERPROOF CANOPY



<i>Self-supporting frame material</i>	<i>Carbon steel sheet, electro-welded, minimum thickness 2,5 mm</i>
<i>Soundproof canopy material</i>	<i>Carbon steel sheet, electro-welded, thickness between 1,5 and 4,5 mm</i>
<i>Painting</i>	<i>Epoxy powder RAL5015 textured, outdoor-proof</i>
<i>In-built fuel tank</i>	<b>120 lt + Drip tray</b>
<i>Soundproofing coating material</i>	<i>Polyester fiber. Fire resistance EN13501-1 class B</i>
<i>Muffler</i>	<i>/</i>
<i>Access openings</i>	<i>n.3 doors with padlockable key lock</i>
<i>Electric panel</i>	<i>Lateral side position. Dedicated door with padlockable key lock</i>
<i>Fresh air intake and hot air expulsion</i>	
<i>Lifting system</i>	<i>n.2 lifting hooks</i>
<i>Support feet</i>	<i>n.4 support feet with holes for machine ground fastening</i>

## CONTAINER TRANSPORTABILITY ADVANTAGES

VERSION	20' BOX	40' BOX	40' HC
 <i>N. transportable pieces</i>	5	10	10
	5	10	10

## MAIN OPTIONS



90A automatic transfer switch (ATS)



250 lt bigger fuel tank with drip tray



750W engine preheating system



Automatic fuel transfer kit with manual by-pass system



Residual current protection relay adjustable in sensitivity and intervention time



Engine oil pressure and cooling water temperature measuring instruments

## OTHER OPTIONS

Power distribution socket set

Synchronizing electric panel

Battery switch

Remote control systems **ETHERNET, 2G - 3G - 4G, GPS**

Further alternator brand

Quick couplings for connecting an external tank with three way valve -

Outdoor, underground and transportable tanks

Slow or fast towing trailer

Front hot air expulsion canopy

Further colors

## VERSIONS WITH SPECIAL EQUIPMENT



### RENTAL

Special version with features designed for the rental market



### ZERO NOISE

Super sound-proofed special version, noise level 50, 55 or 60 dB(A)

**Greenpower AB**  
Helsingborgsvägen Varalöv,  
262 96 Ängelholm, Sweden  
Phone: +46 43122240  
Email: [info@greenpower.se](mailto:info@greenpower.se)  
Web: [www.greenpower.se](http://www.greenpower.se)